

TECHNICAL DATA

PREMIUM PLATFORMS

Width	Length	Weight (kg)		Load distribution (daN/m ²)	
		Thickness 1,25 mm	Thickness 1,5 mm	Thickness 1,25 mm	Thickness 1,5 mm
198 mm	700	5,71	6,23	600	600
	1000	7,33	7,85		
	1500	9,92	10,44		
	2000	12,64	13,16	450	450
	2500	15,23	15,75		
	3000	17,79	18,31		
298 mm	700	6,69	7,35	600	600
	1000	8,63	9,61		
	1500	11,32	12,84		
	2000	14,33	16,39	450	450
	2500	17,02	19,62		
	3000	19,71	22,85		
345 mm	700	7,17	7,88	600	600
	1000	9,29	10,34		
	1500	12,21	13,85		
	2000	15,49	17,71	450	450
	2500	18,41	21,22		
	3000	21,33	24,72		
360 mm	700	7,31	8,02	600	600
	1000	9,47	10,54		
	1500	12,45	14,10		
	2000	15,81	18,05	450	450
	2500	18,79	22,62		
	3000	21,77	25,19		

OPTISSIMO PLATFORMS

Width	Length	Weight (kg)		Load distribution (daN/m ²)	
		Thickness 1,25 mm	Thickness 1,5 mm	Thickness 1,25 mm	Thickness 1,5 mm
298 mm	700	6,69	7,35	600	600
	1000	8,63	9,61		
	1500	11,32	12,84		
	2000	14,33	16,39	450	450
	2500	17,02	19,62		
	3000	19,71	22,85		
345 mm	700	6,23	6,94	600	600
	1000	8,34	9,40		
	1500	11,26	12,90		
	2000	14,54	16,77	450	450
	2500	17,46	20,27		
	3000	20,38	23,78		
360 mm	700	6,25	7,06	600	600
	1000	8,52	9,59		
	1500	11,50	13,15		
	2000	14,86	17,10	450	450
	2500	17,84	20,67		
	3000	20,82	24,24		

Load (daN/m ²)	Class
300	4
450	5
600	6